

# P430i™ Card Printers



## Performance, Reliability, and Expandability in a Dual-Sided Card Printer

The Zebra® P430i is part of Zebra's most popular card printer family, with tens of thousands of printers installed worldwide. Designed and built for demanding environments, the P430i delivers reliability and performance for high-volume card production. Expansion options for networking and card encoding—including UHF Gen 2 for longer read range—gives the P430i the flexibility to meet your specific requirements. Affordable and easy-to-use, the Zebra P430i is a leader in dual-sided performance card printers.

## Ideal for

- Employee ID cards
- Student and faculty ID cards
- Access control cards
- Membership and loyalty cards
- Personalized gift cards
- Visitor ID cards
- Government licenses



# Specifications at a Glance\*

## General Specifications

- 16-character LCD display
- Windows® drivers: 2000, XP, Server 2003; Vista
- Bi-directional driver communication
- One year printer warranty
- One year (unlimited passes) original printhead warranty

## Printing

- Color dye sublimation or monochrome thermal transfer printing
- 102 cards per hour full color dual-sided (YMCKOK)\*\*
- 130 cards per hour full color single-sided (YMCKO)\*\*
- 300 dpi (11.8 dots/mm) print resolution

\*\* Based on average print coverage per card, under certain conditions.

## Bar Codes

- Code 39, Code 128 B & C with & without check digit
- 2-of-5 & 2-of-5 Interleaved
- UPC-A, EAN 8 & EAN 13
- PDF417 2-D bar code and other symbologies can be printed via Windows drivers

## Card Specifications

- Types: PVC, Composite, Adhesive backed
- Card width/length: ISO CR-80-ISO 7810, 2.12"/54 mm x 3.38"/86 mm
- Magnetic Stripe—ISO 7811
- Smart Card contact and contactless
- Card thickness: 10 mil (.25 mm) to 60 mil (1.524 mm)
- Card feeder capacity: 100 cards (30 mil) or 220 cards (30 mil)
- Card output hopper capacity: 100 cards (30 mil)

## Communications Interface

- USB 1.1 (USB 2.0 compatible) cable included
- Optional Built-in 10/100 Ethernet

## Ribbon Specifications

- i Series™ printers require the use of i Series ribbons for full color printing
- YMCKOK: 170 cards/roll
- YMCKO: 200 & 330 cards/roll
- 1/2 Panel YMC Full KO: 450 cards/roll
- KdO and KrO: 500 cards/roll
- Overlay varnishes: Clear and Hologram: 350 cards/roll
- Monochrome: 1500 (Black) & 1000 cards/roll
- Monochrome colors: black, red, blue, green, silver, gold, white and scratch-off grey
- For optimum printer performance use genuine Zebra supplies



## Mechanical

- Width: 26"/660 mm
- Depth: 9.4"/239 mm
- Height: 10.1"/256 mm
- Weight: 20 lbs/9.1 kg

## Electrical

- 100 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- 20 MB image memory standard
- FCC Class A, CE, UL, CUL, and CCC approved

## Environmental



- Operating Temperature: 60° F/15° C to 86° F/30° C
- Operating Humidity: 20% to 65% non-condensing
- Storage Temperature: 23° F/-5° C to 158° F/70° C
- Storage Humidity: 20% to 70% non-condensing
- Ventilation: Free air

## Options

- Built-in 10/100 Mbps Ethernet
- Gen 2 UHF RFID encoder
- Smart card contact-ISO 7816 encoder (30 mil cards only)
- Smart card MIFARE®/DESFire® encoder (30 mil cards only)
- Smart card contact station (30 mil cards only)
- Magnetic encoder (30 mil cards only) 3 track HiCo/LoCo
- High capacity feeder (220 cards)
- Cleaning supplies

## Innovative and Easy to Use

- Easy plug and play USB or USB with Ethernet interface simplifies configuration
- Printhead bracket opens wide for easy ribbon access
- 16 character LCD screen for printer status and error reporting messages
- Translucent card cover allows you to see when supplies are running low and blank cards can be added while printing
- Reject bin holds cards that fail to encode correctly

## Reliable and Flexible

- Prints dual-sided or single-sided
- Revolutionary angled card feeder design means fewer rejected cards
- Self-aligning printhead design for consistently uniform print quality

## Encoding and Network Connectivity

### Expansion Options

- 3 track magnetic stripe encoding (HiCo/LoCo)
- Contact and contactless smart card encoding capabilities
- Built-in 10/100 Ethernet for printer networking simplifies device management and eliminates the need for third party external device.

### High Performance

- Vibrant, true-to-life colors
- High volume card throughput
- Large capacity card feeder available

### i Series™ Functionality

- Automatic color optimization and driver configuration
- Enhanced ribbon formulation for optimal color output

## Genuine Zebra™ Supplies

Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Zebra supplies meet stringent quality standards and are tested for optimum performance with Zebra card printers.



▶ For more information, visit [www.zebra.com](http://www.zebra.com)

\*Specifications subject to change without notice.

©2011 ZIH Corp. i Series and all product names and numbers are Zebra trademarks, and Zebra and the Zebra head graphic are registered trademarks of ZIH Corp. All rights reserved. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. MIFARE is a registered trademark of Philips Semiconductors. Gratkorn GMBH LTD. DESFire is a registered trademark of Koninklijke Philips Electronics N.V. Ltd. All other trademarks are the property of their respective owners.



[www.zebra.com](http://www.zebra.com)